





SISER Print and Cut HTV Time/Temp Chart

HTV Style	Temp.*	Time	Pressure	Peel	Layerable	Dryer Setting
ColorPrint Easy	300°F / 149°C	15 sec.	medium	warm**	no	normal
CP Soft Opaque	311°F / 155°C	15 sec.	medium/firm	hot	no	normal
Hi-5 Print Matte	250°F / 120°C	5 sec.	medium	hot	no	normal
ColorPrint PU	295°F / 146°C	15-20 sec	medium	hot	no	normal
ColorPrint Extra	320°F / 160°C	10-15 sec.	medium	hot	no	normal
CP Sublithin	265°F / 130°C	15 sec.	medium	warm**	no	hang to dry

-  Suitable for cotton, polyesters, blends
-  Suitable for cotton, polyesters, blends, lycra/spandex
-  Suitable for cotton, polyesters, blends, 100% nylon
-  Suitable for cotton, polyesters, blends, sublimated polyester

Snip to it!

Siser Print and Cut Products are not compatible with Inkjet or Laser Printers.
For use with Eco-Solvent, Solvent and Latex Inks only. Consult package for details.

* Siser Print and Cut HTV products cannot be used with a home iron.

** Wait 15 seconds before peeling cover sheet

source: <https://www.siserma.com/files/print-cut-instructions.pdf>